



Visit product page



FOS F9 PRO

L007605

Sophisticated 8-pixel control wall washer, 48X20W 4-IN-1 RGBW LEDs, Flicker free operation, 25 degrees lens and innovative adaptable magnetic barn door, frost, diffuser 40 x 60 degrees, linear dimming, 8/13/16/21/33/48DMX channels, Seetronic IP65 and 3-Pin XLR in/out, OLED display, Active temperature regulated cooling system, Tilt angle manually adjustable, 10 kg

TECHNICAL DETAILS

Product Description

Introducing the sophisticated 8-pixel control wall washer featuring 48X20W 4-IN-1 RGBW LEDs. This cutting-edge lighting fixture offers flicker-free operation, a 25-degree lens, and an innovative adaptable magnetic barn door. Additionally, it includes a frost diffuser with a 40 x 60-degree spread, linear dimming capabilities, and a range of DMX channel options (8/13/16/21/33/48).

Equipped with Seetronic IP65 and 3-Pin XLR in/out connections, an OLED display, and an active temperature-regulated cooling system, this wall washer is designed for professional use. The tilt angle is manually adjustable, allowing for precise positioning, and the fixture weighs 10 kg for easy installation and handling.

Light Source / Optics

Based on 48x 20 Watt 4 in 1 LEDs (RGBW).

Flicker-free operation, suitable for TV and film applications.

25° optics for each LED.

Magnetic frost filter & Barndoors.

Even / soft light output.

Effects

RGBW color mixing.
8 independent segment control.
Preset color macros.
Strobe effects up to 25 Hz.
Smooth dimming.

Control

DMX control with 8, 13, 16, 21, 33 and 48 channels.
Supports RDM.
Seetronic IP65 3-pin XLR inputs and outputs.
1.77" TFT LCD display, with 4 touch buttons.
Temperature-regulated fan control.
Environmental temperature for operation: -25°C to 45°C.
IP65 protection rating.
Maximum power consumption: 1100 Watt.
Power Supply: 100/240 Volt AC, 50/60 Hz.
Net Weight: 10,6 Kg.
Fixture Dimensions: 570 x 150 x 320 mm (D x W x H)

Packing Dimensions

Dimensions: 25 x 36 x 70 cm.
Weight: 16 Kg.

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FC-TP-PDC-5

Professional

TruePowercon/ DMX cable 5 meter.



FC-TP-PDC-1.5

Professional

1.5 meter.



FC-TP-PDC-3

Professional

3 meter.



FOS case F9 PRO

Flight case with wheels for
4 pcs F9 PRO.

